

**Features**

- Slimblade recessed exit with 300 x 150 mm decal
- Plug-in expansion for Emergency Smart driver range
- High Quality Lithium battery (LiFePO<sub>4</sub>) and smart charger
- Wall / surface / pendant or recessed mount options
- Single DALI address for LED driver and emergency
- Single and double sided decals

**Device type 1**

Functions as a maintained IEC62386-202 device

**Low power consumption**

Adds less than a 50 mW to the standby power

**Plug-in upgrade**

Simply plug-in battery and test switch to upgrade device

**Single point unit**

Out of the box the OEM works as a SPU



## Product range

Order code	Description
<b>zc-smart-exit-150</b>	300x150 mm, Emergency exit expansion kit for zc-smart-driver-em*

### Features

- Slimblade recessed exit with 300 x 150 mm decal
- Plug-in expansion for Emergency Smart driver range\*
- High Quality Lithium battery (LiFePO<sub>4</sub>) and smart charger
- Wall / surface / pendant or recessed mount options
- Single DALI address for LED driver and emergency
- Less than 0.75 W average power consumption
- Compliant emergency exit sign

## Kit content

300x150 mm, Emergency exit expansion kit for zc-smart-driver-em\*

1500 mAh, 2 cell, LiFePO<sub>4</sub> battery with holder

Surface mount kit

Wall mount kit

RJ12 connection cable, 1.9 m

## Supported models\*

Order code	Description
<b>zc-smart-driver-em-40</b>	40 W DALI Smart driver with emergency, softwire plug
<b>zc-smart-driver-em-40-t</b>	40 W DALI Smart driver with emergency, screw-terminal
<b>zc-smart-driver-em-40-p</b>	40 W DALI Smart driver with emergency, push-terminal
<b>zc-smart-driver-em-40-au</b>	40 W DALI Smart driver with emergency, 90 min, softwire plug
<b>zc-smart-driver-em-40-au-t</b>	40 W DALI Smart driver with emergency, 90 min, screw-terminal

## Accessory range

Order code	Description
<b>zc-exit-rm-kit</b>	Recessed mount kit
<b>zc-exit-150-decal-kit</b>	300 x 150 mm decal kit

## Specifications

<b>Supply voltage</b>	Powered from zc-smart-driver-em*	
<b>Classification</b>	3	
<b>Wiring</b>	Plug-in loom	
<b>Material</b>	PC (body)	
<b>Mounting</b>	Surface mounted (wall and ceiling), (pendant accessory sold separately)	
<b>Cut-out</b>	Max. 60 mm for Surface mount kit	
<b>Decal size</b>	300 x 150 mm	
<b>Viewing distance</b>	EU 30M AU/NZ 24M	
<b>Operating temperature</b>	0 to 40°C	
<b>Ingress protection</b>	IP20	
<b>Emergency</b>	<b>Rated duration</b>	3 hours
	<b>Testing</b>	Standalone Self test (per IEC62034) DALI Self test (per IEC62386-202)
<b>Battery**</b>	<b>Code</b>	zc-batt-1500mah
	<b>Type</b>	LiFePO <sub>4</sub>
	<b>Voltage</b>	6.4 V
<b>Charger**</b>	<b>Type</b>	Smart charge
	<b>Time</b>	16 hours
	<b>Operation</b>	Multi-state
<b>Compliance standards</b>	IEC 60598-2-22 CISPR 15 IEC 62034 IEC 62386-202	

\*\* Per driver specifications

## Dimensions (mm)

