



Product range

Order code	Description
zc-mw-p	Microwave sensor for zc-smart-driver*

Features

- Plug-in expansion for Smart driver range*
- Functions as IEC62386-303 occupancy sensor
- Ideal for built-in sensor and light batten solutions
- Light control based on motion detection
- Adds < 50 mW additional power consumption to zencontrol driver
- No additional DALI line current

Supported models*

Order code	Description
zc-smart-driver-40	40 W DALI Smart driver, with softwire plug
zc-smart-driver-40-t	40 W DALI Smart driver, with screw terminal
zc-smart-driver-40-p	40 W DALI Smart driver, with push terminal
zc-smart-driver-em-40	40 W DALI Smart driver with emergency, softwire plug
zc-smart-driver-em-40-t	40 W DALI Smart driver with emergency, screw-terminal
zc-smart-driver-em-40-p	40 W DALI Smart driver with emergency, push-terminal
zc-smart-driver-em-40-au	40 W DALI Smart driver with emergency, 90 min, softwire plug
zc-smart-driver-em-40-au-t	40 W DALI Smart driver with emergency, 90 min, screw-terminal

Specifications

Supply	Powered from zc-smart-driver*
Operating power	40 mW
Sensors	Microwave
Frequency	5.8 GHz
Radiated power (EIRP)	0.2 mW
Wiring	Plug-in loom
Material	PC (body)
Detection range	8 m, at 2.7m mounting height
Mounting	Inbuilt
Operating temperature	0 to 45°C
Ingress protection	IP20
Compliance standards	IEC 62386-303

Dimensions

Width	Height	Length
15 mm	19 mm	65 mm

