

Features

- 4 x NO relay output 10A resistive or 6A fluorescent (IEC62386-208)
- Rated inrush of 492A at 1.5ms or 165A at 20ms
- Suitable for distribution board mounting on standard DIN rail
- Protected against DALI over voltage
- LED indicators for system status



DALI device

Fully DALI compliant and compatible



Over-voltage

Protected against DALI over-voltage conditions




Relays

Integrates 4 normally open 10A relays



Interface

Supports DALI-2 and IEC62386-104 over Thread




Product range

Order code	Description
zc-relay-4	4 Channel DALI relay controller

Features

- 4 x NO relay output 10A resistive or 6A fluorescent (IEC62386-208)
- Rated inrush of 492A at 1.5ms or 165A at 20ms
- Suitable for distribution board mounting on standard DIN rail
- Reinforced insulation between DALI and mains supply
- Protected against DALI over voltage
- LED indicators for system status

Dimensions (mm)



Specifications

Supply voltage	220 - 240 V ~ 50 Hz
Control system	Wired DALI-2 Wireless IEC62386-104 over Thread
DALI line current	2 mA
Wiring	1 - 4 mm ² Strip 6 - 7 mm
Operating temperature	0 to 55°C
Material	PC
Classification	Class II
Mounting	DIN rail (35 mm)
Ingress protection	IP20
Compliance standards	IEC 61347-2-11 IEC 60950-1 CISPR 15 CISPR 22 EN 55015 EN 55022 IEC62386-205 IEC62386-208 IEC62386-301/302/303 EMC-2004/108/EC LVD-2006/95/EC

Wiring diagram

