zencontrol

Scenepanel datasheet



Features

- 15 mA DALI line current
- Multiple finishes available
- Up to 10 units per DALI line
- Accessories for 1 4 buttons per plate
- Models to suit 64 and 80 mm mounting centres
- Customisable labels available for specific applications
- Selectable button additions on DALI application controller



Powered by DALI

No additional supply means energy savings and simple installation



Integrated illumination Configurable inbuilt LED

Configurable inbuilt LED status indicator for user convenience



DALI-2

For use with DALI-2 compliant application controller



Configurable

Various button layouts to suit application

zencontrol

Scenepanel datasheet



Product range


Order code	Description
zc-scene-a4	Standard Scenepanel to suit 60 mm wall mount
zc-scene-c-a4	C-clip compatible Scenepanel to suit 84 mm wall mount

Features


- 15 mA DALI line current
- Multiple finishes available
- Up to 10 units per DALI line
- Multiple control devices per line
- Accessories for 1 4 buttons per plate
- Designed for compliance to IEC 62386-301*
- Customisable labels available for specific projects
- For use with DALI-2 compliant application controller
- Control scenes / groups / actions / events with a zencontrol control system

* Pending publication of test sequences

Dimensions




zc-scene-a4 Dimensions 87/87/13 mm Mounting centres 64 mm



zc-scene-c-a4 Dimensions 87/117/13 mm Mounting centres 80 mm

With c-clip

Common configurations



Specifications

Supply	DALI
Control system	DALI-2
DALI line current	15 mA
Wiring	0.5 - 0.75 mm ² Strip 6 - 7 mm
Operating temperature	0 to 45°C
Material	PC UV stabilised, ABS, 316 stainless
Ingress protection	IP20
Compliance standards	IEC 61347-2-11 CISPR 15 IEC 62386-301 EMC-2004/108/EC LVD-2006/95/EC

Notice

- The switch must not be connected to any mains.
 It is powered directly from the DALI line.
- The DALI line is not SELV. It must be treated like LV mains and treated with the same precautions and wiring regulations.
- Compatible with zencontrol control system with a firmware version of 00.08.10 or above

Kit content

zc-scene-a4	
zc-scene-btn-2	2 x blank half button
zc-scene-btn-4	2 x blank quarter button
zc-scene-frm-mult	2 - 4 button frame
zc-scene-fp-st	Brushed stainless faceplate
**Not included	C-clip

Accessory range

Order code	Description
zc-scene-btn-1	Blank single button (note requires zc-scene-frm-s/-c)
zc-scene-btn-2	Blank half button
zc-scene-btn-4	Blank quarter button
zc-scene-frm-s	Single button frame to suit square base
zc-scene-frm-mult	2 - 4 button frame to suit square base
zc-scene-frm-c	Single button frame to suit c-clip base
zc-scene-frm-mult-c	2 - 4 button frame to suit c-clip base
zc-scene-fp-st	Brushed stainless faceplate for standard model
zc-scene-fp-st-c	Brushed stainless faceplate for c-clip model

zencontrol.com Se zencontrol